

**LEED Green Building Submittal Sheet- Metal Trap Tubes and Outlet Waste Ends**



	Description of Section's Relevance	Metal Traps	Cast Brass Metal Traps	Outlet Waste Ends, Tees, And Arms
<b>Product Offerings</b>	Various products offered by Oatey SCS <sup>®</sup> that apply to information as follows.	<ul style="list-style-type: none"> <li>• P-Traps (excluding semi-cast)</li> <li>• Repair Traps</li> <li>• S-Traps (including anti-siphon)</li> <li>• Sink Traps and WM Trap</li> <li>• J-Bends</li> </ul>	<ul style="list-style-type: none"> <li>• N.Y. Code Trap</li> <li>• L.A. Code Trap</li> <li>• Semi-Cast P-Trap</li> </ul>	<ul style="list-style-type: none"> <li>• Outlet Waste Ends</li> <li>• Baffle Tees and Outlet Tees</li> <li>• Outlet Waste Arms</li> </ul>
<b>Low Emitting Materials- VOC Emission Limits</b>	Strictest VOC regulatory limit in which governs the above products.	There are no VOC regulations for these products.	There are no VOC regulations for these products.	There are no VOC regulations for these products.
<b>Low Emitting Materials- Product VOC Content</b>	Best estimate of the actual VOC content within product in g/L or % by weight. Products with low VOC content may assist in earning LEED credit and improving air quality.	These products have no VOC content.	These products have no VOC content.	These products have no VOC content.
<b>Building Product Disclosure- Recycled Content of Materials</b>	Recycled content used within product that may assist in earning LEED points.	There is no recycled content used within these products.	There is no recycled content used within these products.	There is no recycled content used within these products.
<b>PBT<sup>1</sup> Source Reduction-Lead, Cadmium, Copper</b>	Lead, Cadmium, and Copper content for use in determining LEED credit for PBT reduction.	Tubing for these products contains a max 65% copper and 0.07% lead by weight. Brass collars or nuts included contain a max 60% copper and 3% lead.	N.Y. and L.A. code traps contain a max of 60% copper and 3% lead. Semi-Cast P-Traps contain a max of 60% copper and 3% lead for J-Bend and nut and 70% copper 0.07% lead for waste arm.	Outlet waste arms contain a max of 65% copper and 0.07% lead by weight and outlet waste tees contain a maximum of 60% copper and 3% lead by weight.

<b>Red List Content</b>	Any red list materials as defined by the Living Building Challenge (LBC).	These products contain lead in trace amounts and sink traps with PVC adapters contain polyvinyl chloride, both of which are red listed by the LBC.	These products contain lead, which has been red listed by the LBC.	These products contain lead, which has been red listed by the LBC.
<b>Conflict Mineral Content</b>	Any materials within the product that may be from the DRC (Democratic Republic of Congo).	These products contain no conflict minerals.	These products contain no conflict minerals.	These products contain no conflict minerals.
<b>Hazardous Substance Content (ROHS)</b>	Any substances contained within the product reportable per ROHS guidelines.	These products contain small amounts of lead.	These products contain lead.	These products contain lead.
<b>Location(s) Where Manufactured</b>	Manufacturing location of the product pertains to its carbon footprint. If jobsite area is within 500 straight-line miles <sup>2</sup> of this location, LEED credit may be earned.	Locations of manufacturing: <ul style="list-style-type: none"> <li>• Nogales, Mexico</li> </ul>	Locations of manufacturing: <ul style="list-style-type: none"> <li>• Nogales, Mexico</li> </ul>	Locations of manufacturing: <ul style="list-style-type: none"> <li>• Nogales, Mexico</li> </ul>
<b>Additional Information</b>	Additional product information relative to LEED or environmental health and safety.	The lead content in this type of brass tubing is a naturally occurring, trace amount.	There is no additional information for these products.	There is no additional information for these products.

<sup>1</sup>PBT's are known as Persistent Bioaccumulative Toxins.

<sup>2</sup>For use in determining distance between jobsite and manufacturing location in straight-line miles, use tool provided by this link <http://www.daftlogic.com/projects-google-maps-distance-calculator.htm>.

\*All information contained in this document is gathered from reliable sources believed to be up-to-date and accurate to the best of our knowledge.